

DOMUS Suspension

PRODUCT ORDERING CODE



PRODUCT FEATURES

- Oyster white linen shade
- LED engine CRI 90+ available in 2700K | 3000K | 3500K
- White acrylic diffuser at bottom of shade
- LED available with multiple dimming options
- 5 year product warranty on LED products
- Rated for damp location



Project	
Type	
Quantity	
Note	

PRODUCT CODE		LIGHT SOURCE	OAH
DSSPT	Petit Domus Suspension 18" Ø X 9" H Shade	LED28W27K90 28W LED 2700K CRI 90+ 3148 nominal lumens LED28W30K90 28W LED 3000K CRI 90+ 3148 nominal lumens LED28W35K90 28W LED 3500K CRI 90+ 3590 nominal lumens	XX Provide OAH distance from ceiling to the bottom of the luminaire in inches.
DSSSM	Small Domus Suspension 24" Ø X 12" H Shade	LED89W27K90* 89W LED 2700K CRI 90+ 9263 nominal lumens LED89W30K90* 89W LED 3000K CRI 90+ 9263 nominal lumens LED89W35K90* 89W LED 3500K CRI 90+ 10841 nominal lumens	
DSSLG	Large Domus Suspension 30" Ø X 15" H Shade	MB3 3 X 100W 120V Type A-19 incandescent E26 medium base or LED screw-in equivalent (bulbs not included) MB6** 6 X 100W 120V Type A-19 incandescent E26 medium base or LED screw-in equivalent (bulbs not included)	
		* Only available for DSSSM and DSSLG ** Only available with DSSLG only	

DIMMING		VOLTAGE		FINISH	
D010	0-10V 1% dimming LED driver (4 wire)	120V/277V	120V-277V Universal voltage electronic LED driver	21	Polished gold plated
PHS	Forward/Reverse Phase 1% LED dimming driver (2 wire) <i>(only available in 120V)</i>	120V	Electronic LED driver (PHS Phase dimming)	22	Brushed gold plated
NODIM	No dimming option required			24	Brushed nickel plated
				31	Polished nickel plated

CUSTOM MODIFICATIONS


- Sloped ceiling adapter and longer stem
- Customizable finishes, sizes and LED specifications
- Emergency battery pack available
- Dali control protocol or Lutron EcoSystem/3-wire
- Remote driver

DOMUS Suspension

PRODUCT SPECIFICATION



TECHNICAL DRAWING(S)



DIMENSIONS & WEIGHT

DSSPT	H: 9\" W: 18\" Net Wt. 5 lbs.
DSSSM	H: 12\" W: 24\" Net Wt. 5 lbs.
DSSLG	H: 15\" W: 30\" Net Wt. 8 lbs

OTHER SPECIFICATIONS

- Standard stem 5/8\" Ø X 48\" (not field cuttable, must specify required OAH)
- Overall height (DSSPT = 57\") - (DSSSM = 60\") - (DSSLG = 63\")
- Canopy size 5\" Ø X 0.63"

INSTALLATION REQUIREMENTS

- Mounts to a standard 4\" octagonal electrical junction box or plaster ring
- Driver concealed within shade

LIGHT SOURCE SPECIFICATIONS

- Electronic constant current LED power supply
- Consistent binning that falls within 3 MacAdam ellipse
- LED Life, L70 > 84 700 hrs at 70% lumen maintenance
- Integral Class II driver concealed within shade
- Thermally managed within manufacturer specifications to maximize LED life
- Field replacement for LED module and driver is simple & requires minimal effort
- LED module made in Canada
- No ultraviolet or infrared, alleviating potential damage to art, fabric & materials
- Electrical components are mercury free and are RoHS compliant

COMPATIBLE DIMMER LIST

Compatibility dimmer list available on our website:
www.hemeralighting.com/dimming