

JUPITER Ceiling Fixture

PRODUCT ORDERING CODE



PRODUCT FEATURES

- Hand-blown 7" Ø clear frosted glass globe
- CREE COB CRI 90+ available in 2700K | 3000K | 3500K | 4000K
- Magnetic canopy with no apparent fastener offered in 2 size options
- Customizable sizes, finishes and LED specifications
- 5 year product warranty on LED products
- Rated for damp location



Project

Type

Quantity

Note

PRODUCT CODE	LIGHT SOURCE	CANOPY & REMOTE DRIVER
JPC Jupiter Ceiling Fixture H: 8.5" x W: 7" Ø	COB9W27K90 9W LED 2700K CRI 90+ 1025 nominal lumens	CM 5" Ø canopy (LED driver in junction box) Remote driver option with Standard Round canopy 5" Ø x 0.625" REM-CM REM-MCC Remote driver with one micro 2" Ø canopy REMOTE DRIVER OPTION Remote driver option requires a separate remote box. Referes to REM spec sheet for details.
	COB9W30K90 9W LED 3000K CRI 90+ 1087 nominal lumens	
	COB9W35K90 9W LED 3500K CRI 90+ 1141 nominal lumens	
	COB9W40K90 9W LED 1000K CRI 90+ 1141 nominal lumens	

DIMMING	VOLTAGE	FINISH
D010 0-10V 1% dimming LED driver (4 wire) PHS Forward/Reverse Phase 1% LED dimming driver (2 wire) <i>(only available in 120V)</i> NODIM No dimming option required	120V/277V 120V-277V Universal voltage electronic LED driver 120V Electronic LED driver (PHS Phase dimming)	01 White paint 02 Black paint 08 Dark mat bronze paint 12 Antique gold paint 21 Polished gold plated 22 Brushed gold plated 24 Brushed nickel plated 31 Polished nickel plated 33 Black polished nickel chrome

CUSTOM MODIFICATIONS



- Customizable finishes, sizes and LED specifications

JUPITER Ceiling Fixture



PRODUCT SPECIFICATION



TECHNICAL DRAWING(S)



CM



REM-MCC

DIMENSIONS & WEIGHT

JPC H: 8.5" W: 7" Ø Net Wt. 4 lbs.

OTHER SPECIFICATIONS

- CM canopy size is 5" Ø x 0.25" H (except for REM-MCC)
- Canopy size for REM-MCC option is 2" Ø x 0.25" H
- UL Certified and suitable for damp location

INSTALLATION REQUIREMENTS

- Driver to be fitted in junction box (except for remote options)
- Mounts to a standard 4" octagonal electrical junction box or plaster ring (except for remote options)
- REM-MC canopy option requires a 1.375" Ø hole, ceiling thickness up to 1"

LIGHT SOURCE SPECIFICATIONS

- Electronic constant current LED power supply
- COB CREE LED: consistent binning that falls within 2 MacAdam ellipse
- COB Life, L70 > 61 000 hrs at 70% lumen maintenance
- Integral Class II driver
- Thermally managed within manufacturer specifications to maximize LED life
- No ultraviolet or infrared, alleviating potential damage to art, fabric & materials
- Electrical components are mercury free and are RoHS compliant

COMPATIBLE DIMMER LIST

Compatibility dimmer list available on our website:
www.hemeralighting.com/dimming


JUPITER Ceiling Fixture

PRODUCT SPECIFICATION

PHOTOMETRIC DATA

COB9W35K90

Nominal LED Source Wattage: 9W
System wattage: 9.98W
Color accuracy: CRI 90+
Light Color: 3500° K
Delivered lumens: 903.6 lm
Luminaire efficacy: 90.5 lm/w



COLOR TEMP. MULTIPLIER

2700K	0.93
3000K	1.97
3500K	1.00
4000K	1.04