


PASTIS Ceiling Fixture

PRODUCT ORDERING CODE



PRODUCT FEATURES

- Hand-blown white opal satin glass shade 6.5" Ø x 3.25" H
- LED engine CRI 90+ available in 2700K | 3000K | 3500K
- Multiple plated & painted finishes
- LED available with multiple dimming options
- 5 year product warranty on LED products
- Rated for damp location

Project

Type

Quantity

Note



PRODUCT CODE		LIGHT SOURCE	
PAC	Pastis Ceiling Fixture - H: 3.5" W: 6.5" Ø	LED9W27K90	9W LED 2700K CRI 90+ 1275 nominal lumens
		LED9W30K90	9W LED 3000K CRI 90+ 1310 nominal lumens
		LED9W35K90	9W LED 3500K CRI 90+ 1315 nominal lumens


DIMMING		VOLTAGE		FINISH	
D010	0-10V 1% dimming LED driver (4 wire)	120V/277V	120V-277V Universal voltage electronic LED driver	01	White paint
				02	Black paint
				08	Dark mat bronze paint
PHS	Forward/Reverse Phase 1% LED dimming driver (2 wire) <i>(only available in 120V)</i>	120V	Electronic LED driver (PHS Phase dimming)	12	Antique gold paint
				21	Polished gold plated
				22	Brushed gold plated
NODIM	No dimming option required			24	Brushed nickel plated
				31	Polished nickel plated
				33	Black polished nickel plated

CUSTOM MODIFICATIONS


- Emergency battery pack available
- Dali control protocol or Lutron compact fluorescent dimming options
- Customizable finishes and LED specifications
- Remote driver

PASTIS Ceiling Fixture

PRODUCT SPECIFICATION



TECHNICAL DRAWING(S)



DIMENSIONS & WEIGHT

PAC H: 3.5" W: 6.5" Ø Net Wt. 3 lbs.

OTHER SPECIFICATIONS

- Canopy size 4.5" Ø
- Center of electrical junction box to side of fixture 3.25"
- UL Certified and suitable for damp location

INSTALLATION REQUIREMENTS

- Driver to be fitted in junction box
- Mounts to a standard 4" octagonal electrical junction box or plaster ring

LIGHT SOURCE SPECIFICATIONS

- Electronic constant current LED power supply
- Consistent binning that falls within 3 MacAdam ellipse
- LED Life, L70 > 60 000 hrs at 70% lumen maintenance
- Integral Class II driver
- Thermally managed within manufacturer specifications to maximize LED life
- No ultraviolet or infrared, alleviating potential damage to art, fabric & materials
- Electrical components are mercury free and are RoHS compliant

COMPATIBLE DIMMER LIST

Compatibility dimmer list available on our website:
www.hemeralighting.com/dimming


PASTIS Ceiling Fixture

PRODUCT SPECIFICATION

PHOTOMETRIC DATA

LED9W35K90

Nominal LED Source Wattage: 9W
System wattage: 11.3W
Color accuracy: CRI 90+
Light Color: 3500° K
Delivered lumens: 907.4 lm
Luminaire efficacy: 80.0 lm/w



COLOR TEMP. MULTIPLIER

2700K	0.96
3000K	0.98
3500K	1.00
4000K	1.04