

WESTMOUNT Suspension

PRODUCT ORDERING CODE



PRODUCT FEATURES

- Multiple shade options with encapsulated fabrics and materials in high performance resin
- LED engine CRI 90+ available in 2700K | 3000K | 3500K
- White acrylic diffuser at bottom of shade
- Perforated grid on top of shade
- LED available with multiple dimming options
- 5 year product warranty on LED products
- Rated for damp location



Project	
Type	
Quantity	
Note	

PRODUCT CODE	LIGHT SOURCE	OAH
WSS Westmount Suspension H: 10" W (A): 38" W (B): 8"	LED28W27K90 28W LED 2700K CRI 90+ 3252 nominal lumens LED28W30K90 28W LED 3000K CRI 90+ 3252 nominal lumens LED28W35K90 28W LED 3500K CRI 90+ 3710 nominal lumens LED41W27K90 41W LED 2700K CRI 90+ 4424 nominal lumens LED41W30K90 41W LED 3000K CRI 90+ 4424 nominal lumens LED41W35K90 41W LED 3500K CRI 90+ 5044 nominal lumens MB 2 X 60W 120V Type A-19 incandescent E26 medium base or LED screw-in equivalent (bulbs not included)	XX Provide OAH distance from ceiling to the bottom of the luminaire in inches. (Min. 15", max. 58")

SHADE	DIMMING	VOLTAGE	FINISH
AC White satin finish acrylic KN Imago progeny blonde encapsulated fabric KW Lintel white encapsulated linen SW Sand dollar white encapsulated linen	D010 0-10V 1% dimming LED driver (4 wire) PHS Forward/Reverse Phase 1% LED dimming driver (2 wire) <i>(only available in 120V)</i> NODIM No dimming option required	120V/277V 120V-277V Universal voltage electronic LED driver 120V Electronic LED driver (PHS Phase dimming)	01 White paint 02 Black paint 08 Dark mat bronze paint 21 Polished gold plated 24 Brushed nickel plated 31 Polished nickel plated

✕ CUSTOM MODIFICATIONS


- Longer stems
- Customizable finishes, sizes and LED specifications
- Emergency battery pack available, inquire for details
- Dali control protocol or Lutron EcoSystem/3-wire dimming (28W option only)
- Remote driver

WESTMOUNT Suspension

PRODUCT SPECIFICATION



TECHNICAL DRAWING(S)



DIMENSIONS & WEIGHT

WSS H: 10" W (A): 38" W (B): 8" Net Wt. 38 lbs.

OTHER SPECIFICATIONS

- Standard stems 5/8" Ø X 48" (not field cuttable, must specify required OAH)
- Standard maximum overall height 58.375"
- Canopy size 4.5" X 16"
- Position of electrical junction box centered on canopy
- UL Certified and suitable for damp location

INSTALLATION REQUIREMENTS

- Mounts to a standard 4" octagonal electrical junction box or plaster ring
- Driver concealed within fixture

LIGHT SOURCE SPECIFICATIONS

- Electronic constant current LED power supply
- Consistent binning that falls within 3 MacAdam ellipse
- LED Life, L70 > 84 700 hrs at 70% lumen maintenance
- Integral Class II driver concealed within shade
- Thermally managed within manufacturer specifications to maximize LED life
- LED engine made in Canada
- No ultraviolet or infrared, alleviating potential damage to art, fabric & materials
- Electrical components are mercury free and are RoHS compliant

© COMPATIBLE DIMMER LIST

Compatibility dimmer list available on our website:
www.hemeralighting.com/dimming