

CHLOE Suspension

PRODUCT ORDERING CODE



PRODUCT FEATURES

- Hand-blown white opal satin glass shade 6.5" Ø x 3.25" H
- Painted reflecting saucer
- LED engine CRI 90+ available in 2700K | 3000K | 3500K
- Cord option is available in various colours
- LED available with multiple dimming options
- Available with 2 canopy options
- Fixture height is adjustable
- 5 year product warranty on LED products
- Rated for damp location



Project	
Type	
Quantity	
Note	

PRODUCT CODE	LIGHT SOURCE	CORD	CANOPY & REMOTE DRIVER
CESSM Small Chloe Suspension 10" Ø X 6.75" H Shade	LED9W27K90 9W LED 2700K CRI 90+ 1275 nominal lumens	AGC Anthracite gray cord	RC Round Canopy 5" Ø X 0.625" (driver in junction box)
CESMD Medium Chloe Suspension 16.75" Ø X 6.75" H Shade	LED9W30K90 9W LED 3000K CRI 90+ 1310 nominal lumens	PWC Pearly white cord	REM-MC Remote driver option with micro 2" Ø canopy
CESLG Large Chloe Suspension 24" Ø X 6.75" H Shade	LED9W35K90 9W LED 3500K CRI 90+ 1315 nominal lumens	SBC Silky black cord	REM-RC Remote driver option with Round Canopy 5" Ø X 0.625"
			ⓘ REMOTE DRIVER OPTION <i>Remote driver option requires a separate remote box. Refers to REM spec sheet for ordering details.</i>

DIMMING	VOLTAGE	FINISH
D010 0-10V 1% dimming LED driver (4 wire)	120V/277V 120V-277V Universal voltage electronic LED driver	01 White paint
PHS Forward/Reverse Phase 1% LED dimming driver (2 wire) <i>(only available in 120V)</i>	120V Electronic LED driver (PHS Phase dimming)	02 Black paint
NODIM No dimming option required		08 Dark mat bronze paint
		12 Antique gold paint

✂ CUSTOM MODIFICATIONS

- Electronic constant current LED power supply
- Consistent binning that falls within 3 MacAdam ellipse
- LED Life, L70 > 60 000 hrs at 70% lumen maintenance
- 5 year product warranty on LED products
- Rated for damp location
- Integral Class II driver
- Thermally managed within manufacturer specifications to maximize LED life
- No ultraviolet or infrared, alleviating potential damage to art, fabric & materials
- Electrical components are mercury free and are RoHS compliant

CHLOE Suspension

PRODUCT SPECIFICATION



DIMENSIONS & WEIGHT

CESM	H: 6.75" W: 10" Net Wt. 3 lbs.
CESMD	H: 6.75" W: 16.75" Net Wt. 4 lbs.
CESLG	H: 6.75" W: 24" Net Wt. 6 lbs.

OTHER SPECIFICATIONS

- Standard 72" long color cord is field adjustable (AGC, PWC, SBC, SGC)
- Standard canopy size is 5" Ø x 0.63" H (except for REM-MC)
- Canopy size for REM-MC option is 2" Ø x 0.25" H
- Maximum overall height 78" (field adjustable)



INSTALLATION REQUIREMENTS

- Driver to be fitted in junction box (except for remote option)
- Mounts to a standard 4" octagonal electrical junction box or plaster ring (except for remote options)
- REM-MC canopy option requires a 1.375" Ø hole, ceiling thickness up to 1"

LIGHT SOURCE SPECIFICATIONS





- Electronic constant current LED power supply
- Consistent binning that falls within 3 MacAdam ellipse
- LED Life, L70 > 60 000 hrs at 70% lumen maintenance
- Integral Class II driver
- Thermally managed within manufacturer specifications to maximize LED life
- No ultraviolet or infrared, alleviating potential damage to art, fabric & materials
- Electrical components are mercury free and are RoHS compliant

TECHNICAL DRAWING(S)





CESM

CESM REM-MC





CESMD

CESMD REM-MC



CESLG



CESLG REM-MC

COMPATIBLE DIMMER LIST


Compatibility dimmer list available on our website:
www.hemeralighting.com/dimming

CHLOE Suspension

PRODUCT SPECIFICATION

PHOTOMETRIC DATA

LED9W35K90
Nominal LED Source Wattage: 9W
Nominal light output: 1315 lm
System wattage: 11.32W
Color accuracy: CRI 90+
Light Color: 3500° K
Delivered lumens: 1024.8 lm
Luminaire efficacy: 90.5 lm/w



COLOR TEMP. MULTIPLIER	
2700K	0.95
3000K	1.00
3500K	1.05
4000K	1.09